



NOTES:

1. FIXED BOLLARDS SHALL BE TRAFFICGUARD RFP SERIES, AND REMOVABLE BOLLARDS SHALL BE TRAFFICGUARD RP3500 SERIES, OR APPROVED EQUAL. BOLLARDS SHALL BE FINISHED WITH POWDER COATED BLACK PAINT.
2. BOLLARDS AND SIGNS SHALL BE INSTALLED PER MANUFACTURER DETAILS AND SPECIFICATIONS.
3. CONCRETE FOUNDATIONS SHALL BE CONSTRUCTED TO WITHSTAND 6,000 LBS OF STATIC LOAD AT 27 INCHES ABOVE GRADE PER MANUFACTURER SPECIFICATIONS.
4. BOLLARDS SHALL BE INSTALLED OUTSIDE THE CLEAR ZONE WHEN ADJACENT TO ROADWAY. BOLLARDS SHALL BE INSTALLED MINIMUM 10 FEET FROM THE BACK OF CURB RAMP WHEN APPLICABLE.
5. PROVIDE A 2-FOOT SEPARATION BETWEEN TRAIL AND BOLLARDS WHEN TRAIL IS 8 FEET IN WIDTH.
6. FIXED BOLLARDS SHALL NOT BE REQUIRED WHEN MOTOR VEHICLE ACCESS IS BLOCKED BY PEDESTRIAN RAILING OR FENCING.