



NOTES

1. WARNING SIGNS TO BE MADE OF DURABLE WATERPROOF MATERIAL.
2. ALL LETTERS TO BE AT LEAST 3-INCHES HIGH, CLEARLY LEGIBLE AND SPACED AS INDICATED ABOVE.
3. SIGNS TO BE PLACED 200-FEET ON CENTER, MAX.
4. SIGNS TO BE PLACED AT EACH END OF LINEAR TREE PROTECTION AREA AND 200-FEET ON CENTER THEREAFTER.
5. FOR TREE PROTECTION AREAS LESS THAN 200-FEET IN PERIMETER, PROVIDE NO LESS THAN ONE SIGN PER PROTECTION AREA AND/OR SIDE.
6. ATTACH SIGNS SECURELY TO FENCE POSTS AND FABRIC.
7. FABRIC MUST BE ATTACHED TO APPROVED POSTS ONLY. DO NOT ATTACH TO TREES.
8. MAINTAIN TREE PROTECTION FENCE THROUGHOUT DURATION OF PROJECT - FENCING MUST REMAIN UPRIGHT AND SLACK FREE.
9. ADDITIONAL SIGNS AND/OR PROTECTION MEASURES MAY BE REQUIRED BY THE PLANNING DEPARTMENT BASED UPON ACTUAL FIELD CONDITIONS.
10. FAILING TO MAINTAIN TREE PROTECTION MEASURES MAY RESULT IN FINES AND/OR PERMIT REVOCATION.

**TOWN OF APEX
STANDARDS**

TREE PROTECTION FENCE

STD. NO.

200.06

EFFECTIVE: FEBRUARY 28, 2023

SHEET 1 OF 1